



# SF-150D

## Dimple Top 1" Pitch

Category 1 Replacement for:  
Intralox 1600 & 1650NT

\*Non-Headed Rods



Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
1"	.47"	4"	.20"	0%	Yes	No
25.4mm	12mm	101.6mm	5.2mm			

  

Belt Material	Standard Rod Material	Belt Strength		Temperature Fahrenheit		Belt Weight Lb/Ft <sup>2</sup>	Colors
		Straight Lb/Ft	Curved Lb/Ft	Min	Max		
PP	PP	705	-	34°	220°	1.15	W, G, B
PE	PE	355	-	-50°	150°	1.2	N, B
POM	PE	1005	-	-50°	150°	1.75	N, B
ULTRA-TUFF™	ULT	940	-	32°	302°	1.73	N, W, DB
ULTRA-TUFF XMD™	ULT	940	-	32°	302°	1.92	RB

  

# of Teeth	PD	Bore Size
6	2"	1"RD
8	2.5"	1"RD
10	3.2"	1.5"
12	3.9"	1.5"
18	5.1"	1.5"
20	6.4"	1.5"

  

Additional Sprockets Available	
Belt Standard Alterations	+/- .5"
Flight Standard Indent	+/- 1.5"



W-White, B-Blue, DB-Dark Blue, RB-Royal Blue, N-Natural, G-Gray, BK-Black, BR-Brown, XMD-XRAY & Metal Detectable



A CHIORINO GROUP COMPANY